

View Online at <https://aerobasegroup.com/nsn/4140-00-059-7575>

**Speed Adjustments:**

Single speed

**Length:**

2.312 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Weatherproof

**Ambient Temperature At Full Rated Power:**

-65.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

22000.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking and radio interference shielding

**Air Flow Rate:**

162.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

135.0 watts

**Housing Inside Diameter:**

2.625 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Surface Treatment:**

Enamel

**Style Designator:**

Fixed

**Fsc Application Data:**

Power supply, guided missile remote control system, airborne

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0