

View Online at <https://aerobasegroup.com/nsn/4140-00-059-8567>

Speed Adjustments:

Single speed

Width:

3.340 inches

Length:

2.680 inches

Environmental Protection:

Humidity proof and shock proof and vibration proof and salt spray resistant

Ambient Temperature At Full Rated Power:

-20.0 degrees celsius and 50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

8500.0

Electrical Connection Type:

Terminal block

Outlet Inside Width:

1.250 inches

Outlet Inside Height:

1.375 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 3 threaded insert

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

26.0 cubic feet per minute

Outlet Location:

Bottom or top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.037 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Special Features:

Positioning when mtg by thd inserts and tapped holes in motor flat determines discharge blast direction, class f insulation motor windings

Frequency In Hertz:

400.0

Height:

3.050 inches

Material:

Steel blade

Surface Treatment:

Zinc blade

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0