

View Online at <https://aerobasegroup.com/nsn/4140-00-061-8702>

**Speed Adjustments:**

Three speed

**Width:**

4.690 inches

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Ambient Temperature At Full Rated Power:**

-25.0 degrees fahrenheit and 175.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

1600.0

**End Application:**

Highspeed printer, miltope corporation model hsp3609/212a

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

Between 55.0 cubic feet per minute and 75.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.002 horsepower

**Housing Inside Diameter:**

4.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

Wire color coded blue white and green, gas modified by wire lead electrical connection and special features

**Frequency In Hertz:**

50.0 and 60.0 and 400.0

**Height:**

4.690 inches

**Material:**

Plastic polycarbonate blade

**Surface Treatment:**

Enamel housing

**Surface Treatment Specification:**

Tt-e-489 military specification single treatment response housing

**Style Designator:**

Fixed

**Specification Or Standard:**

-23071/7-003 type

**Departure From Cited Designator (non-core):**

As modified by wire lead electrical connection and special features

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

spec.