NSN 4140-00-067-7460

Centrifugal Fan - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4140-00-067-7460 |
|---|
| Speed Adjustments: |
| Single speed |
| Width: |
| 15.250 inches |
| Length: |
| 13.250 inches |
| Ambient Tempurature At Full Rated Power: |
| -20.0 degrees celsius and 55.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 3450.0 |
| Electrical Connection Type: |
| Wire lead |
| Outlet Inside Width: |
| 4.937 inches |
| Outlet Inside Height: |
| 5.375 inches |
| Static Pressure At Specificationified Air Flow Rate: |
| 0.0 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 1 base plate |
| Rotation Direction For Which Designed: |
| Clockwise |
| Features Provided: |
| Nonsparking |
| Air Flow Rate: |
| 1300.0 cubic feet per minute |
| Outlet Location: |
| Тор |
| Voltage In Volts And Current Type: |
| 195.0 ac or 255.0 ac |
| Prime Mover Power Rating: |
| 1.608 horsepower |

Sleeve

Discharge Direction:

Prime Mover Drive Shaft Bearing Type:

Angular up

NSN 4140-00-067-7460Centrifugal Fan - Page 2 of 2



| Phase: |
|---|
| Three |
| Special Features: |
| Duct clamps furnished for outlet and inlet, discharge blast 30 degrees from vertical when mtd by motor base plate on horizontal surface |
| operating altitude 0 to 10000 ft |
| Frequency In Hertz: |
| 50.0 and 60.0 |
| Height: |
| 15.375 inches |
| Material: |
| Steel |
| Surface Treatment: |
| Enamel housing outside |
| Style Designator: |
| Fixed, rectangular outlets |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A087a0 |
| |
| |