NSN 4140-00-073-9186

Tubeaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-073-9186

| Speed Adjustments: |
|--|
| Single speed |
| Length: |
| 2.469 inches |
| Flow Direction: |
| Outward |
| Environmental Protection: |
| Vibration proof |
| Ambient Tempurature At Full Rated Power: |
| -55.0 degrees celsius and 85.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 3750.0 |
| Electrical Connection Type: |
| Terminal block |
| Static Pressure At Specificationified Air Flow Rate: |
| 0.4 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 3 clamp and 2 rim |
| Rotation Direction For Which Designed: |
| Clockwise |
| Features Provided: |
| Nonsparking |
| Air Flow Rate: |
| 325.0 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 115.0 ac |
| Prime Mover Power Rating: |
| 0.041 horsepower |
| Housing Inside Diameter: |
| 6.812 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |
| Product Name: |
| Fan, saucer type |
| Phase: |
| Single |

NSN 4140-00-073-9186

Tubeaxial Fan - Page 2 of 2



| Frequency In Hertz: |
|--|
| 400.0 |
| Material: |
| Aluminum alloy |
| Surface Treatment: |
| Enamel |
| Surface Treatment Specification: |
| Tt-e-489 federal specification single treatment response |
| Style Designator: |
| Fixed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A087a0 |