

View Online at <https://aerobasegroup.com/nsn/4140-00-081-4364>

**Speed Adjustments:**

Single speed

**Width:**

4.109 inches

**Length:**

3.625 inches

**Environmental Protection:**

Fungus resistant and humidity proof and shock proof and vibration proof and salt spray resistant

**Operating Speed At Rated Capacity In Rpm:**

3100.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

1.406 inches

**Outlet Inside Height:**

1.468 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

3 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

20.0 cubic feet per minute

**Outlet Location:**

Bottom and top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.018 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Single

**Special Features:**

Positioning when mtg determines discharge blast direction

**Frequency In Hertz:**

60.0

**Height:**

3.750 inches

**Material:**

Steel

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0