

View Online at <https://aerobasegroup.com/nsn/4140-00-081-4364>

Speed Adjustments:

Single speed

Width:

4.109 inches

Length:

3.625 inches

Environmental Protection:

Fungus resistant and humidity proof and shock proof and vibration proof and salt spray resistant

Operating Speed At Rated Capacity In Rpm:

3100.0

Electrical Connection Type:

Wire lead

Outlet Inside Width:

1.406 inches

Outlet Inside Height:

1.468 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

3 threaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

20.0 cubic feet per minute

Outlet Location:

Bottom and top

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.018 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular down and angular up and horizontal and vertical down and vertical up

Phase:

Single

Special Features:

Positioning when mtg determines discharge blast direction

Frequency In Hertz:

60.0

Height:

3.750 inches

Material:

Steel

Surface Treatment:

Zinc blade

Style Designator:

Fixed, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0