NSN 4140-00-083-1120

Centrifugal Fan - Page 1 of 2

Speed Adjustments:

Single speed



View Online at https://aerobasegroup.com/nsn/4140-00-083-1120

Width:
19.000 inches
Length:
6.250 inches
Environmental Protection:
Fungus resistant and moisture resistant and salt spray resistant
Ambient Tempurature At Full Rated Power:
-20.0 degrees fahrenheit and 250.0 degrees fahrenheit
Operating Speed At Rated Capacity In Rpm:
3100.0
Electrical Connection Type:
Wire lead
Outlet Inside Width:
1.625 inches
Outlet Inside Height:
2.125 inches
Static Pressure At Specificationified Air Flow Rate:
0.0 inches of water
Drive Type:
Direct
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Fully enclosed Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 2 flange and 8 slot
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed:
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate:
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 150.0 cubic feet per minute
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 150.0 cubic feet per minute Outlet Location:
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 150.0 cubic feet per minute Outlet Location: Top
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 150.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type:
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 150.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 150.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating:
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 150.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 70.0 watts Prime Mover Drive Shaft Bearing Type: Ball
Mounting Facility Type And Quantity: 2 flange and 8 slot Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 150.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 70.0 watts Prime Mover Drive Shaft Bearing Type:

NSN 4140-00-083-1120 Centrifugal Fan - Page 2 of 2



Phase:
Single
Special Features:
ncludes washable inlet filter and stainless steel inlet grill
Frequency In Hertz:
50.0 and 60.0
Height:
5.250 inches
Material:
Steel
Quantity:
1
Surface Treatment:
Cadmium blade
Style Designator:
Fixed, dual, rectangular outlets
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4087a0