NSN 4140-00-083-6060

Centrifugal Fan - Page 1 of 2

Stage Quantity:

Single speed

11.094 inches **Length:**

Width:

Speed Adjustments:



View Online at https://aerobasegroup.com/nsn/4140-00-083-6060

| Environmental Protection: Moisture resistant Ambient Tempurature At Full Rated Power: 55.0 degrees celsius Operating Speed At Rated Capacity In Rpm: 3700.0 Electrical Connection Type: Terminal Outlet Inside Width: 3.844 inches Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Ellectric motor Inclosure Type: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise Features Provided: |
|---|
| Ambient Tempurature At Full Rated Power: 55.0 degrees celsius Operating Speed At Rated Capacity In Rpm: 3700.0 Electrical Connection Type: Terminal Outlet Inside Width: 3.844 inches Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| 55.0 degrees celsius Operating Speed At Rated Capacity In Rpm: 3700.0 Electrical Connection Type: Terminal Outlet Inside Width: 3.844 inches Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Ellectric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Operating Speed At Rated Capacity In Rpm: 3700.0 Electrical Connection Type: Terminal Outlet Inside Width: 3.844 inches Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Electrical Connection Type: Terminal Outlet Inside Width: 3.844 inches Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Electrical Connection Type: Terminal Outlet Inside Width: 3.844 inches Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Terminal Outlet Inside Width: 3.844 inches Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Outlet Inside Width: 3.844 inches Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| 3.844 inches Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Outlet Inside Height: 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| 4.500 inches Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Static Pressure At Specificationified Air Flow Rate: 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| 4.2 inches of water Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Drive Type: Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Fully enclosed Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Mounting Facility Type And Quantity: 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| 4 unthreaded hole Rotation Direction For Which Designed: Counterclockwise |
| Rotation Direction For Which Designed: Counterclockwise |
| Counterclockwise |
| |
| Features Provided: |
| |
| Safety impeller guard and nonsparking |
| Outlet Location: |
| Тор |
| Voltage In Volts And Current Type: |
| 115.0 ac |
| Prime Mover Power Rating: |
| 0.670 horsepower |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |
| |

NSN 4140-00-083-6060 Centrifugal Fan - Page 2 of 2



| Discharge Direction: |
|----------------------------|
| Vertical up |
| Phase: |
| Three |
| Height: |
| 10.844 inches |
| Material: |
| Steel housing |
| Quantity: |
| 1 |
| Surface Treatment: |
| Paint housing outside |
| Style Designator: |
| Fixed, rectangular outlets |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A087a0 |
| |