

View Online at <https://aerobasegroup.com/nsn/4140-00-087-1877>

**Speed Adjustments:**

Single speed

**Length:**

1.734 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Humidity proof

**Operating Speed At Rated Capacity In Rpm:**

11000.0

**End Application:**

Supply class aoe; ticonderoga class cg (47); spruance class dd (963); forrestal class cv; tactical air opns module (an/tyq (23); radar (highpar) an/gpn-22 (v); aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130) ; kidd class ddg; helicopter, sof/hh-53h pace low

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

190.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.040 horsepower

**Housing Inside Diameter:**

3.500 inches

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Unpackaged Unit Weight:**

1.000 pounds

**Surface Treatment:**

Enamel

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0