

View Online at <https://aerobasegroup.com/nsn/4140-00-087-1877>

Speed Adjustments:

Single speed

Length:

1.734 inches

Flow Direction:

Outward

Environmental Protection:

Humidity proof

Operating Speed At Rated Capacity In Rpm:

11000.0

End Application:

Supply class aoe; ticonderoga class cg (47); spruance class dd (963); forrestal class cv; tactical air opns module (an/tyq (23); radar (highpar) an/gpn-22 (v); aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130) ; kidd class ddg; helicopter, sof/hh-53h pace low

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

190.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.040 horsepower

Housing Inside Diameter:

3.500 inches

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Unpackaged Unit Weight:

1.000 pounds

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0