

View Online at <https://aerobasegroup.com/nsn/4140-00-088-7999>

Speed Adjustments:

Single speed

Length:

2.469 inches

Flow Direction:

Reversible

Environmental Protection:

Explosion proof

Operating Speed At Rated Capacity In Rpm:

3250.0

Electrical Connection Type:

Connector receptacle

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

270.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

25.000 watts

Housing Inside Diameter:

5.750 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Test set, guided missile

Frequency In Hertz:

50.0 and 60.0

Material:

Aluminum alloy

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0