

View Online at <https://aerobasegroup.com/nsn/4140-00-102-8607>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

1.352 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Fungus proof and humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

22500.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.6 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 rim

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

10.000 cubic feet per minute

**Voltage In Volts And Current Type:**

26.0 dc

**Prime Mover Power Rating:**

0.012 horsepower

**Housing Inside Diameter:**

Between 1.123 inches and 1.125 inches

**Material:**

Aluminum alloy

**Quantity:**

1

**Surface Treatment:**

Anodize

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0