

View Online at <https://aerobasegroup.com/nsn/4140-00-105-3083>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

1.500 inches

Length:

1.468 inches

Flow Direction:

Outward

Environmental Protection:

Corrosion resistant and fungus resistant and moisture resistant and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

10000.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

9.300 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.008 horsepower

Housing Inside Diameter:

1.562 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize or chromate

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response or mil-c-5541 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.