

View Online at <https://aerobasegroup.com/nsn/4140-00-105-3083>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

1.500 inches

**Length:**

1.468 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Corrosion resistant and fungus resistant and moisture resistant and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

10000.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

9.300 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.008 horsepower

**Housing Inside Diameter:**

1.562 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Anodize or chromate

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response or mil-c-5541 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.