

View Online at <https://aerobasegroup.com/nsn/4140-00-105-8391>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

2.625 inches

Length:

Between 2.281 inches and 2.343 inches

Flow Direction:

Outward

Environmental Protection:

Fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

0.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11600.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 ring

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

82.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.032 horsepower

Housing Inside Diameter:

Between 2.802 inches and 2.822 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Quantity:

1

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.