

View Online at <https://aerobasegroup.com/nsn/4140-00-107-8185>

Speed Adjustments:

Single speed

Length:

Between 8.370 inches and 8.490 inches

Flow Direction:

Inward

Environmental Protection:

Corrosion resistant and dustproof and fungus resistant and humidity proof and moisture resistant and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-28.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11000.0

Electrical Connection Type:

Cord w/attached plug

Static Pressure At Specificationified Air Flow Rate:

5.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

1100.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

977.500 watts

Housing Inside Diameter:

7.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Paint

Style Designator:

Fixed

Test Data Document:

10001-2890762-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A087a0