## NSN 4140-00-122-6422

Centrifugal Fan - Page 1 of 2

**Speed Adjustments:** 

Single speed



View Online at https://aerobasegroup.com/nsn/4140-00-122-6422

Width:
4.594 inches
Length:
4.469 inches
Environmental Protection:
Dustproof
Ambient Tempurature At Full Rated Power:
-28.0 degrees celsius and 75.0 degrees celsius
Operating Speed At Rated Capacity In Rpm:
3450.0
Electrical Connection Type:
Terminal block
Outlet Inside Width:
2.156 inches
Outlet Inside Height:
1.922 inches
Static Pressure At Specificationified Air Flow Rate:
0.5 inches of water
Drive Type:
Direct
Prime Mover Type:
Prime Mover Type: Electric motor
••
Electric motor
Electric motor Inclosure Type:
Electric motor Inclosure Type: Fully enclosed
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 49.0 cubic feet per minute
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 49.0 cubic feet per minute Outlet Location:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 49.0 cubic feet per minute Outlet Location: Top
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 49.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 49.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 49.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating:
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 49.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 47.0 watts
Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 2 unthreaded hole Rotation Direction For Which Designed: Clockwise Air Flow Rate: 49.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 115.0 ac Prime Mover Power Rating: 47.0 watts Prime Mover Drive Shaft Bearing Type:

## NSN 4140-00-122-6422

Centrifugal Fan - Page 2 of 2



Pnase:
Single
Frequency In Hertz:
50.0 and 60.0
Height:
4.813 inches
Material:
Steel housing
Surface Treatment:
Paint housing outside
Style Designator:
Fixed, inverted, rectangular outlet
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:

A087a0