

View Online at <https://aerobasegroup.com/nsn/4140-00-133-1780>

**Speed Adjustments:**

Single speed

**Length:**

1.730 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Explosion proof

**Operating Speed At Rated Capacity In Rpm:**

3450.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

58.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.014 horsepower

**Housing Inside Diameter:**

3.219 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Material:**

Aluminum alloy

**Unpackaged Unit Weight (non-core):**

1.000 pounds

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-5557, type 4 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5557 spec.