

View Online at <https://aerobasegroup.com/nsn/4140-00-134-9116>

Speed Adjustments:

Single speed

Length:

1.608 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 91.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11000.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

34.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

20.500 watts

Housing Inside Diameter:

1.990 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Surface Treatment:

Enamel

Style Designator:

Fixed

Test Data Document:

05257-905898-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0