

View Online at <https://aerobasegroup.com/nsn/4140-00-145-7334>

Speed Adjustments:

Single speed

Length:

1.540 inches

Flow Direction:

Outward

Environmental Protection:

Moisture resistant

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

22500.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 rim

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

12.0 cubic feet per minute

Voltage In Volts And Current Type:

26.0 ac

Prime Mover Power Rating:

0.017 horsepower

Housing Inside Diameter:

2.141 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Mtg rim located on discharge end

Frequency In Hertz:

400.0

Material:

Plastic blade

Style Designator:

Fixed

Test Data Document:

06481-917088-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A087a0