

View Online at <https://aerobasegroup.com/nsn/4140-00-168-1871>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

2.125 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

16500.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

1.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

3 lug and 3 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

34.000 cubic feet per minute

Voltage In Volts And Current Type:

26.0 dc or 30.0 dc

Prime Mover Power Rating:

0.040 horsepower

Housing Inside Diameter:

1.875 inches

Material:

Aluminum

Quantity:

1

Surface Treatment:

Enamel

Style Designator:

Fixed

Test Data Document:

82050-22786 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0