

View Online at <https://aerobasegroup.com/nsn/4140-00-195-6230>

Speed Adjustments:

Single speed

Length:

6.200 inches

Flow Direction:

Outward

Ambient Temperature At Full Rated Power:

0.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

7500.0

Electrical Connection Type:

Connector receptacle

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

315.0 cubic feet per minute

Voltage In Volts And Current Type:

208.0 ac

Prime Mover Power Rating:

1.090 horsepower

Housing Inside Diameter:

5.060 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize blade

Surface Treatment Specification:

Mil-e-15090, type 1, cl 2 military specification single treatment response housing outside or mil-e-15090, type 2, cl 2 military specification single treatment response housing outside

Style Designator:

Fixed

Test Data Document:

24930-g830038s3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.