

View Online at <https://aerobasegroup.com/nsn/4140-00-195-6230>

**Speed Adjustments:**

Single speed

**Length:**

6.200 inches

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

0.0 degrees celsius and 65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

7500.0

**Electrical Connection Type:**

Connector receptacle

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

315.0 cubic feet per minute

**Voltage In Volts And Current Type:**

208.0 ac

**Prime Mover Power Rating:**

1.090 horsepower

**Housing Inside Diameter:**

5.060 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Anodize blade

**Surface Treatment Specification:**

Mil-e-15090, type 1, cl 2 military specification single treatment response housing outside or mil-e-15090, type 2, cl 2 military specification single treatment response housing outside

**Style Designator:**

Fixed

**Test Data Document:**

24930-g830038s3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.