NSN 4140-00-202-5901

Centrifugal Fan - Page 1 of 2

Stage Quantity:



View Online at https://aerobasegroup.com/nsn/4140-00-202-5901

Speed Adjustments:
Single speed
Width:
34.875 inches
Diameter:
15.250 inches
Length:
27.438 inches
Environmental Protection:
Splash proof
Ambient Tempurature At Full Rated Power:
50.0 degrees celsius
Operating Speed At Rated Capacity In Rpm:
1750.0
Outlet Inside Width:
11.750 inches
Outlet Inside Height:
16.375 inches
Static Pressure At Specificationified Air Flow Rate:
2.0 inches of water
Date Tone
Drive Type:
Direct
Direct
Direct Prime Mover Type:
Direct Prime Mover Type: Electric motor
Direct Prime Mover Type: Electric motor Inclosure Type:
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity:
Direct Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole
Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole Rotation Direction For Which Designed:
Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole Rotation Direction For Which Designed: Clockwise
Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole Rotation Direction For Which Designed: Clockwise Features Provided:
Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole Rotation Direction For Which Designed: Clockwise Features Provided: Nonsparking
Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole Rotation Direction For Which Designed: Clockwise Features Provided: Nonsparking Air Flow Rate:
Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole Rotation Direction For Which Designed: Clockwise Features Provided: Nonsparking Air Flow Rate: 2000.0 cubic feet per minute
Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole Rotation Direction For Which Designed: Clockwise Features Provided: Nonsparking Air Flow Rate: 2000.0 cubic feet per minute Outlet Location:
Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole Rotation Direction For Which Designed: Clockwise Features Provided: Nonsparking Air Flow Rate: 2000.0 cubic feet per minute Outlet Location: Top
Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Mounting Facility Type And Quantity: 6 unthreaded hole Rotation Direction For Which Designed: Clockwise Features Provided: Nonsparking Air Flow Rate: 2000.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type:

NSN 4140-00-202-5901 Centrifugal Fan - Page 2 of 2



Prime Mover Drive Shaft Bearing Type:
Ball
Discharge Direction:
Horizontal
Height:
32.813 inches
Material:
Steel housing
Quantity:
1
Surface Treatment:
Zinc housing outside
Style Designator:
Fixed, rectangular outlets
Reference Number Differentiating Characteristics:
As differentiated by westinghouse controller dwg no. 1-je-2497
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
4087a0