

View Online at <https://aerobasegroup.com/nsn/4140-00-209-7957>

Speed Adjustments:

Single speed

Width:

14.690 inches

Length:

1.430 inches

Environmental Protection:

Humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-10.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3600.0

Electrical Connection Type:

Terminal block

Outlet Inside Width:

5.560 inches

Outlet Inside Height:

5.620 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 threaded hole

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Safety impeller guard and thermal protective device

Air Flow Rate:

1800.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

4000.0 watts

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Three

Special Features:

Plain inlet ring w/guard

Frequency In Hertz:

400.0

Height:

13.310 inches

Material:

Aluminum

Surface Treatment:

Enamel housing outside

Style Designator:

Fixed, inverted, rectangular outlet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0