

View Online at <https://aerobasegroup.com/nsn/4140-00-209-7965>

**Speed Adjustments:**

Single speed

**Width:**

14.690 inches

**Length:**

1.430 inches

**Environmental Protection:**

Humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-10.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3600.0

**Electrical Connection Type:**

Terminal block

**Outlet Inside Width:**

5.560 inches

**Outlet Inside Height:**

5.620 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

1800.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

4000.0 watts

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical up

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Height:**

13.310 inches

**Material:**

Aluminum

**Surface Treatment:**

Enamel

**Style Designator:**

Fixed, inverted, rectangular outlet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0