

View Online at <https://aerobasegroup.com/nsn/4140-00-226-4258>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

1.891 inches

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Dustproof and humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

15600.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 clamp ring

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

20.0 cubic feet per minute

**Voltage In Volts And Current Type:**

55.0 ac

**Prime Mover Power Rating:**

0.036 horsepower

**Housing Inside Diameter:**

1.990 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

Sq wave voltage

**Frequency In Hertz:**

800.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Anodize

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0