

View Online at <https://aerobasegroup.com/nsn/4140-00-226-4258>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

1.891 inches

Length:

1.500 inches

Flow Direction:

Inward

Environmental Protection:

Dustproof and humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

15600.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 clamp ring

Rotation Direction For Which Designed:

Counterclockwise

Features Provided:

Nonsparking

Air Flow Rate:

20.0 cubic feet per minute

Voltage In Volts And Current Type:

55.0 ac

Prime Mover Power Rating:

0.036 horsepower

Housing Inside Diameter:

1.990 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Sq wave voltage

Frequency In Hertz:

800.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0