

View Online at <https://aerobasegroup.com/nsn/4140-00-226-6591>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Diameter:**

1.859 inches

**Length:**

1.600 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Explosion proof

**Ambient Temperature At Full Rated Power:**

125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

19500.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

60.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.042 horsepower

**Housing Inside Diameter:**

1.890 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Anodize

**Special Test Features:**

Mil-e-5272, procedure vi, condition d

**Style Designator:**

Fixed

**Test Data Document:**

06481-900289-15 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5272 spec.