

View Online at <https://aerobasegroup.com/nsn/4140-00-228-9005>

Speed Adjustments:

Single speed

Width:

3.625 inches

Length:

Between 1.438 inches and 1.562 inches

Flow Direction:

Outward

Environmental Protection:

Fungus resistant and moisture resistant

Ambient Temperature At Full Rated Power:

0.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

2800.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

45.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac or 230.0 ac

Prime Mover Power Rating:

18.400 watts

Housing Inside Diameter:

3.250 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Height:

3.625 inches

Material:

Zinc housing

Material Specification:

Qq-z-363 federal specification single material response housing

Surface Treatment:

Enamel housing

Surface Treatment Specification:

Tt-e-529 federal specification single treatment response housing

Style Designator:

Fixed

Test Data Document:

92755-176-39-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0