

View Online at <https://aerobasegroup.com/nsn/4140-00-231-1475>

Speed Adjustments:

Single speed

Length:

1.500 inches

Flow Direction:

Outward

Environmental Protection:

Moisture resistant

Ambient Temperature At Full Rated Power:

-30.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3500.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

50.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.020 horsepower

Housing Inside Diameter:

3.000 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

4.688 in. Sq flange both ends venturi tube

Frequency In Hertz:

400.0

Material:

Zinc alloy housing

Surface Treatment:

Enamel semigloss housing

Style Designator:

Fixed

Test Data Document:

30003-247asc0317-002 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0