View Online at https://aerobasegroup.com/nsn/4140-00-242-0902

Speed Adjustments:

Single speed

Length:

1.500 inches

Flow Direction:

Inward

Ambient Tempurature At Full Rated Power:

-28.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

5300.0

Electrical Connection Type:

Connector receptacle

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

190.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.044 horsepower

Housing Inside Diameter:

4.125 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

4.690 in. Sq flange both ends venturi tube

Frequency In Hertz:

400.0

Material:

Plastic polycarbonate blade

Surface Treatment:

Enamel blade

Style Designator:

Fixed

Test Data Document:

05869-717454-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0