

View Online at <https://aerobasegroup.com/nsn/4140-00-254-7255>

**Speed Adjustments:**

Single speed

**Width:**

3.690 inches

**Length:**

Between 3.880 inches and 4.000 inches

**Environmental Protection:**

Fungus resistant and humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-28.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

5500.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Diameter:**

1.250 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

23.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.016 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Height:**

Between 3.750 inches and 3.870 inches

**Material:**

Steel

**Surface Treatment:**

Cadmium blade

**Style Designator:**

Fixed, round outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0