

View Online at <https://aerobasegroup.com/nsn/4140-00-262-8249>

**Stage Quantity:**

1

**Speed Adjustments:**

Two speed

**Diameter:**

13.250 inches

**Length:**

16.250 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Splash proof

**Ambient Temperature At Full Rated Power:**

50.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

1750.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

2.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

2100.0 cubic feet per minute

**Voltage In Volts And Current Type:**

440.0 ac

**Prime Mover Power Rating:**

1.500 horsepower

**Housing Inside Diameter:**

17.000 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Material:**

Aluminum housing

**Quantity:**

1

**Style Designator:**

Fixed

**Reference Number Differentiating Characteristics:**

As differentiated by cutler hammer controller dwg no. D922-1-1m4

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0