

View Online at <https://aerobasegroup.com/nsn/4140-00-262-8249>

Stage Quantity:

1

Speed Adjustments:

Two speed

Diameter:

13.250 inches

Length:

16.250 inches

Flow Direction:

Inward

Environmental Protection:

Splash proof

Ambient Temperature At Full Rated Power:

50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

1750.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

2.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

2100.0 cubic feet per minute

Voltage In Volts And Current Type:

440.0 ac

Prime Mover Power Rating:

1.500 horsepower

Housing Inside Diameter:

17.000 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

60.0

Material:

Aluminum housing

Quantity:

1

Style Designator:

Fixed

Reference Number Differentiating Characteristics:

As differentiated by cutler hammer controller dwg no. D922-1-1m4

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0