

View Online at <https://aerobasegroup.com/nsn/4140-00-267-0780>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Environmental Protection:**

Dripproof

**Ambient Temperature At Full Rated Power:**

50.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

1750.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

2.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

500.0 cubic feet per minute

**Outlet Location:**

Bottom

**Voltage In Volts And Current Type:**

115.0 dc

**Prime Mover Power Rating:**

0.750 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Material:**

Steel blade

**Quantity:**

1

**Reference Number Differentiating Characteristics:**

As differentiated by ajlg and csbh

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0