View Online at https://aerobasegroup.com/nsn/4140-00-267-0967

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

15.375 inches

Flow Direction:

Inward

Environmental Protection:

Explosion proof

Ambient Tempurature At Full Rated Power:

65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3450.0

Electrical Connection Type:

Cord w/attached plug

Static Pressure At Specificationified Air Flow Rate:

2.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

500.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.333 horsepower

Housing Inside Diameter:

Between 10.495 inches and 10.505 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

60.0

Material:

Aluminum housing

Quantity:

1

Surface Treatment:

Chromate zinc

Style Designator:

Fixed

Specification Or Standard:

O type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0