

View Online at <https://aerobasegroup.com/nsn/4140-00-267-0968>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Length:**

15.375 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Explosion proof

**Ambient Temperature At Full Rated Power:**

50.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3450.0

**Electrical Connection Type:**

Cord w/attached plug

**Static Pressure At Specificationified Air Flow Rate:**

2.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

500.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 dc

**Prime Mover Power Rating:**

0.333 horsepower

**Housing Inside Diameter:**

Between 10.495 inches and 10.505 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Material:**

Aluminum

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-2934 military specification single treatment response

**Style Designator:**

Fixed

**Specification Or Standard:**

O type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-e-2934 spec.