

View Online at <https://aerobasegroup.com/nsn/4140-00-267-1077>

Stage Quantity:

1

Speed Adjustments:

Single speed

Environmental Protection:

Dripproof

Ambient Temperature At Full Rated Power:

40.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

1505.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

4.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Nonsparking

Air Flow Rate:

4000.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

250.0 dc

Prime Mover Power Rating:

5.000 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Material:

Steel blade

Quantity:

1

Surface Treatment:

Zinc

Reference Number Differentiating Characteristics:

As differentiated by csbh and cutler hammer controller dwg-942-1-1m1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0