## NSN 4140-00-267-2032

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-267-2032

| Stage Quantity:                                      |
|--|
| 1  |
| Speed Adjustments:                                   |
| Single speed   |
| Diameter:  |
| 25.000 inches  |
| Length:  |
| 69.250 inches  |
| Flow Direction:                                      |
| Outward  |
| Operating Speed At Rated Capacity In Rpm:            |
| 6200.0   |
| Electrical Connection Type:                          |
| Terminal block                                       |
| Static Pressure At Specificationified Air Flow Rate: |
| 35.0 inches of water                                 |
| Drive Type:  |
| Direct   |
| Prime Mover Type:                                    |
| Steam turbine  |
| Inclosure Type:                                      |
| Fully enclosed                                       |
| Mounting Facility Type And Quantity:                 |
| 1 flange   |
| Rotation Direction For Which Designed:               |
| Counterclockwise                                     |
| Air Flow Rate:                                       |
| 25500.0 cubic feet per minute                        |
| Prime Mover Power Rating:                            |
| 227.000 horsepower                                   |
| Housing Inside Diameter:                             |
| 47.500 inches  |
| Material:  |
| Steel housing  |
| Quantity:  |
| 1  |
| Surface Treatment:                                   |
| Zinc housing outside                                 |
| Style Designator:                                    |
| Fixed  |
| Reference Number Differentiating Characteristics:    |
| As differentiated by Ih blower connection            |

## NSN 4140-00-267-2032

Vaneaxial Fan - Page 2 of 2



| _ |     |      |   |        |  |
|---|-----|------|---|--------|--|
| c | hο  | JIF. |   | .ife:  |  |
| J | 116 |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A087a0