

View Online at <https://aerobasegroup.com/nsn/4140-00-269-3189>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

10.468 inches

Length:

15.375 inches

Flow Direction:

Inward

Environmental Protection:

Splash proof

Ambient Temperature At Full Rated Power:

50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3450.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

2.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

550.0 cubic feet per minute

Voltage In Volts And Current Type:

440.0 ac

Prime Mover Power Rating:

0.333 horsepower

Housing Inside Diameter:

10.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

60.0

Material:

Steel housing

Quantity:

1

Surface Treatment:

Paint housing inside

Style Designator:

Fixed

Reference Number Differentiating Characteristics:

As differentiated by peerles motor dwg no. M-3037

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0