

View Online at <https://aerobasegroup.com/nsn/4140-00-269-5236>

Stage Quantity:

1

Speed Adjustments:

Single speed

Diameter:

25.000 inches

Length:

25.625 inches

Flow Direction:

Inward

Environmental Protection:

Splash proof

Ambient Temperature At Full Rated Power:

50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

1765.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

3.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

6000.000 cubic feet per minute

Voltage In Volts And Current Type:

440.0 ac

Prime Mover Power Rating:

5.000 horsepower

Housing Inside Diameter:

25.250 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

60.0

Material:

Steel housing

Quantity:

1

Surface Treatment:

Zinc housing outside

Style Designator:

Fixed

Reference Number Differentiating Characteristics:

As differentiated by westinghouse controller, dwg no. 37-j-337

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0