

View Online at <https://aerobasegroup.com/nsn/4140-00-269-5793>

Stage Quantity:

1

Speed Adjustments:

Single speed

Environmental Protection:

Dripproof

Ambient Temperature At Full Rated Power:

50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

1750.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

2.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

500.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

115.0 dc

Prime Mover Power Rating:

0.750 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Material:

Steel housing

Quantity:

1

Surface Treatment:

Zinc housing outside

Reference Number Differentiating Characteristics:

As differentiated by ajlg and cutler hammer controller dwg 909-31m2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0