

View Online at <https://aerobasegroup.com/nsn/4140-00-269-7920>

**Speed Adjustments:**

Single speed

**Diameter:**

4.750 inches

**Length:**

5.9375 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Dustproof

**Ambient Temperature At Full Rated Power:**

Not rated

**Operating Speed At Rated Capacity In Rpm:**

7400.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

2 flange

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

240.0 cubic feet per minute

**Voltage In Volts And Current Type:**

105.0 ac or 125.0 ac

**Prime Mover Power Rating:**

0.066 horsepower

**Housing Inside Diameter:**

5.562 inches

**Prime Mover Drive Shaft Bearing Type:**

Sleeve

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Quantity:**

1

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.