

View Online at <https://aerobasegroup.com/nsn/4140-00-277-4169>

**Stage Quantity:**

1

**Environmental Protection:**

Shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-20.0 degrees celsius and 80.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

7200.0

**Outlet Inside Diameter:**

0.875 inches

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Nonsparking

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.010 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Single

**Special Features:**

Aluminum wire mesh on elevator mounted

**Material:**

Steel blade

**Quantity:**

1

**Surface Treatment:**

Cadmium blade

**Style Designator:**

Fixed, round outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0