

View Online at <https://aerobasegroup.com/nsn/4140-00-289-4304>

**Stage Quantity:**

1

**Speed Adjustments:**

Two speed

**Width:**

33.000 inches

**Length:**

33.000 inches

**Environmental Protection:**

Spray tight

**Ambient Temperature At Full Rated Power:**

149.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

1800.0

**End Application:**

W/s: nimitz class cvn; arleigh burke class ddg; oliver perry class ffg; tarawa class lha; wasp class lhd; emory s. Land class as; supply class aoe; ticonderoga class cg (47); forrestal class cv

**Outlet Inside Width:**

11.750 inches

**Outlet Inside Height:**

19.625 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 pedestal and 6 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

3000.0 cubic feet per minute

**Outlet Location:**

Bottom or top

**Voltage In Volts And Current Type:**

440.0 ac

**Prime Mover Power Rating:**

3.000 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular down and angular up and horizontal and vertical down and vertical up

**Phase:**

Three

**Height:**

41.250 inches

**Material:**

Steel housing

**Quantity:**

1

**Surface Treatment:**

Chromate zinc housing and varnish housing

**Style Designator:**

Fixed, rectangular outlets

**Specification Or Standard:**

Cc type and 3a4w6ccwns code

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0