NSN 4140-00-289-4315

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-289-4315 **Speed Adjustments:** Single speed Length: 29.625 inches Flow Direction: Outward **Environmental Protection:** Watertight **Ambient Tempurature At Full Rated Power:** 65.0 degrees celsius **Operating Speed At Rated Capacity In Rpm:** 1750.0 **Electrical Connection Type:** Terminal block Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Mounting Facility Type And Quantity:** 1 flange **Rotation Direction For Which Designed:** Clockwise **Features Provided:** Safety impeller guard Air Flow Rate: 3000.0 cubic feet per minute **Voltage In Volts And Current Type:** 440.0 ac **Prime Mover Power Rating:** 3.000 horsepower **Housing Inside Diameter:** 23.250 inches **Prime Mover Drive Shaft Bearing Type:** Ball Phase: Three

Frequency In Hertz: 60.0

NSN 4140-00-289-4315

Vaneaxial Fan - Page 2 of 2

Mil-std (military Standard):

Mil-f-18953 spec.



Material:
Steel housing
Material Specification:
Qq-a-250/11 federal specification single material response blade
Surface Treatment:
Zinc housing outside
Style Designator:
Fixed
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A087a0