Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-00-289-8783

| Speed Adjustments: |
|--|
| Single speed |
| Length: |
| 37.875 inches |
| Flow Direction: |
| Outward |
| Ambient Tempurature At Full Rated Power: |
| 65.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 1750.0 |
| Electrical Connection Type: |
| Terminal block |
| Static Pressure At Specificationified Air Flow Rate: |
| 0.0 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 1 flange |
| Rotation Direction For Which Designed: |
| Clockwise |
| Features Provided: |
| Safety impeller guard |
| Voltage In Volts And Current Type: |
| 440.0 ac |
| Prime Mover Power Rating: |
| 10.000 horsepower |
| Housing Inside Diameter: |
| 31.250 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Steel housing |
| Material Specification: |
| Qq-a-250/11 federal specification single material response blade |
| |

NSN 4140-00-289-8783

Vaneaxial Fan - Page 2 of 2



Style Designator:

Fixed

Test Data Document:

81349-milf18953 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Shelf Life:**

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-f-18953 spec.