

View Online at <https://aerobasegroup.com/nsn/4140-00-289-8826>

Speed Adjustments:

Single speed

Length:

8.000 inches

Flow Direction:

Outward

Environmental Protection:

Spray tight

Ambient Temperature At Full Rated Power:

65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3450.0

End Application:

W/s: forrestal class cv; oliver perry class ffg; tarawa class lha; wasp class; arleigh burke class ddg; spruance class dd (963); ticonderoga class cg (47); nimitz class cvn; kidd class ddg

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.7 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

380.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.066 horsepower

Housing Inside Diameter:

8.000 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

As modified by push button or rotary switch included

Frequency In Hertz:

60.0

Material:

Steel housing

Unpackaged Unit Weight:

60.000 pounds

Style Designator:

Fixed

Departure From Cited Designator (non-core):

As modified by push button or rotary switch included

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-f-18953 spec.